



## **BACK-UP SIGHT**

Non-powered direct sight for armored vehicles


Nedinsco's BACK-UP SIGHT provides the crew of armored vehicles with the ability to engage targets in degraded mode. The non-powered BACK-UP SIGHT is an emergency device and is TRL-9. Available in both Single Field of View and Dual Field of View models, this non-powered direct sighting device is suitable for new and retrofit programs for armored vehicles. The BACK-UP SIGHT can be customized to be used with different caliber guns and in a variation of military vehicles.


## **KEY FEATURES**

- Targeting and situational awareness in degraded mode
- Non-powered direct sight with integrated reticle and laser filter
- Flexible, high quality optical fiber bundle
- Spoof proof
- Easy integration



## **DETECTION | RECOGNITION | IDENTIFICATION**







## **TECHNICAL SPECIFICATIONS – BACK-UP SIGHT**

		COBRA LR D-FOV	COBRA MR D-FOV	PYTHON S-FOV
MECHANICAL DI	MENSIONS			
Eyepiece (HxWxL)		119x86x142 mm (4.7x3.4 x 5.6")	120x105x172 mm (4.8x4.2x6.8")	55x55x178 mm (2.2x2.2x7")
Objective (HxWxL)		138 x 90 x 180 mm (5.4x3.5x7.1")	139x133x164 mm (5.5x5.3x6.5")	56x62x173 mm (2.2x2.5x6.9")
Optical fiber	Length		0.6 – 4.5 m (24 - 180")	
	Feed through hole armor		Ø40 mm (Ø1.58")	
	Bending radius		R152mm (R6")	
Weight (1)		7.6 kg (16.8 lb)	7.6 kg (16.8 lb)	3 kg (6.6 lb)
OPTICAL				
Narrow Field Of View (HxV)		2.2x1.6°	2.95x2.2°	2.2x1.6°
Wide Field Of View (HxV)		21.7x16.3°	20x15°	N/A
System Magnification - Zoom		1x, 10x	1.08x, 7.4x	10x
Exit pupil diameter			Ø6 mm (Ø0.24")	
Eye relief position			20 mm (0.79")	
Diopter adjustment			±4D	
Optical fiber resolution			670x500 or 500x670	
Laser filter (2)			OD5, λ694 & 1064 nm	
Reticle	Adjustment	±1.4 mil	±3.8 mil	N/A
	Design (2)		Cross	
	Illumination (2)		Optional red LED	
ENVIRONMENTA	L			
Operating temperature		-46°C (-50.8F) to +71°C (+159.8F)		
Environmental standard			MIL-STD-810F	

(1) Based on 72" (1.8m) optical fiber; (2) Customer specific solutions possible











© 2021 - This technical datasheet is copyright of Nedinsco B.V. and contains proprietary information which shall not be used, reproduced or disclosed to third parties without prior written authorization by Nedinsco B.V. and its suppliers/customers. Data on this sheet may be subject to change without notification as a result of ongoing technical development. All rights reserved.